

# Allargatori ▪ Svasatori

ALIX  
PRECISION



Core Drills ▪ Countersinks



ALIX<sup>®</sup>  
PRECISION



# DIN 343



## Allargatori a 3 taglienti con attacco conico, in HSS

Core drills with 3 flutes and straight shank made of HSS



Tipo / Type					N
Esecuzione elica Cutting direction					
Materiale / Material					HSS
Ø mm h8	L <sub>1</sub> mm	L <sub>2</sub> mm	Ø minimo preforo Min. hole size	CM MT	6251
7,80	156	75	5,6	1	●
8,00	156	75	5,6	1	●
8,80	162	81	6,3	1	●
9,00	162	81	6,3	1	●
9,80	168	87	7,0	1	●
10,00	168	87	7,0	1	●
10,75	175	94	7,7	1	●
11,00	175	94	7,7	1	●
11,75	175	94	8,4	1	●
12,00	182	101	8,4	1	●
12,75	182	101	9,1	1	●
13,00	182	101	9,1	1	●
13,75	189	108	9,8	1	●
14,00	189	108	9,8	1	●
14,75	212	114	10,5	2	●
15,00	212	114	10,5	2	●
15,75	218	120	11,2	2	●
16,00	218	120	11,2	2	●
16,75	223	125	11,9	2	●
17,00	223	125	11,9	2	●
17,75	228	130	12,6	2	●
18,00	228	130	12,6	2	●
18,70	233	135	13,3	2	●
19,00	233	135	13,3	2	●
19,70	238	140	14,0	2	●
20,00	238	140	14,0	2	●
20,70	243	145	14,6	2	●
21,00	243	145	14,6	2	●
21,70	248	150	15,3	2	●
22,00	248	150	15,3	2	●
22,70	253	155	16,0	2	●
23,00	253	155	16,0	2	●
23,70	281	160	16,6	3	●
24,00	281	160	16,6	3	●
24,70	281	160	17,3	3	●
25,00	281	160	17,3	3	●
25,70	286	165	18,0	3	●
26,00	286	165	18,0	3	●
26,70	291	170	18,6	3	●
27,00	291	170	18,6	3	●

Tipo / Type					N
Esecuzione elica Cutting direction					
Materiale / Material					HSS
Ø mm h8	L <sub>1</sub> mm	L <sub>2</sub> mm	Ø minimo preforo Min. hole size	CM MT	6251
27,70	291	170	19,3	3	●
28,00	291	170	19,3	3	●
28,70	296	175	20,0	3	●
29,00	296	175	20,0	3	●
29,70	296	175	20,5	3	●
30,00	296	175	20,5	3	●
30,60	301	180	21,0	3	●
31,00	301	180	21,0	3	●
31,60	306	185	22,0	3	●
32,00	334	185	22,0	4	●
32,60	334	185	23,0	4	●
33,00	334	185	23,0	4	●
33,60	339	190	24,0	4	●
34,00	339	190	24,0	4	●
34,60	339	190	25,0	4	●
35,00	339	190	25,0	4	●
35,60	344	195	25,5	4	●
36,00	344	195	25,5	4	●
36,60	344	195	26,0	4	●
37,00	344	195	26,0	4	●
37,60	349	200	26,5	4	●
38,00	349	200	26,5	4	●
38,60	349	200	27,0	4	●
39,00	349	200	27,0	4	●
39,60	349	200	28,0	4	●
40,00	349	200	28,0	4	●
40,60	354	205	28,5	4	●
41,00	354	205	28,5	4	●
41,60	354	205	29,0	4	●
42,00	354	205	29,0	4	●
42,60	359	210	30,0	4	●
43,00	359	210	30,0	4	●
43,60	359	210	30,5	4	●
44,00	359	210	30,5	4	●
44,60	359	210	31,0	4	●
45,00	359	210	31,0	4	●
45,60	364	215	32,0	4	●
46,00	364	215	32,0	4	●
46,60	364	215	32,5	4	●
47,00	364	215	32,5	4	●

Per misure intermedie prezzi a richiesta / Deviating sizes prices upon request

● Utensile disponibile a magazzino / Items available ex stock







